## **United States Patent**

## Wilson III

Golf ball lifter and tee setting device

Inventer: Byron R. Wilson III 4151 Tee Circle In & TR

Sarasota, Fl. 34235

Appl. No.

Filed: Jan. 30, 2004

Inst. CL -----

U.S. Cl. ----

Field of search ----

References Cited U.S. Patent documents

Inventer [	Patent No.	[ Date of patent
Brandt et al.	6,254,497 B1	July 3, 2001
Jack Palmer	6,053,821	April 25, 2000
Timothy M. Peterson	6, 004, 227	December 21, 1999
David R. Corriveau	5,928,091	July 27, 1999
Sun Ho Park	5, 913, 737	June 22, 1999
T. Lee Dahlmann	5,772,533	June 30, 1998
Charles Erickson Jr.	5,759,117	June2, 1998
Berkowitz et al.	5,707303	<b>Janurary 13, 1998</b>
Joseph Cretella	5,645,498	<b>July 8,1997</b>
Nichols etal.	5,632,696	May 27, 1997
Richard D. Keller	5,540,432	July 30, 1996
Rodger W. Ahner	5,494,279	Februrary 27, 1996

## Patent Number Date of Patent

JUL 1 5 2004

Lottie K. Vogrin	5,165,744	November 24, 1992
August H. Wolf	5, 080,357	Janurary 14, 1992
Wesley J Tobias	4,969,646	November 13, 1990
James F. Kopfie	4,951,947	August 27, 1990
Clyde E. Henthorn	4,714,250	December 22, 1987
John E. Murdock	3, 671,037	June 20, 1972

Primary Examiner: Charles Chandler

## **Abstract**

A pocket size small light hinged golf ball pick up and tee placement device clips on to the grip of most any golf club. It is disclosed here to allow a golfer to repeadely pick up golf balls and place them on the tee at the driving range or out on the golf course. The fold up open ring ballholder is shaped with two down facing semilunar curved prongs that easily slides under and around the golf ball to pick it up off any surface and place it on the tee. The tee chamber firmly holds the tee within a tapered conical released platform that conforms the the taper of the flange of the tee which is kept from wobbling by a second semicircular notched platform below that closly fits around the shaft of the tee. The tee can then be firmly placed into the ground at any desired depth. The grip chamber holds the grip of the golf club with a close fitting socket at the end with two flexable flat flanged prongs farther up the grip.

4 claims, 5 drawing sheets

